

Ghost



A recessed profile for ground installation, particularly durable and reliable, **ideal for use in drive-over areas**. The AISI 316 stainless steel casing ensures resistance to adverse climatic conditions and makes it suitable for high salinity environments.

Passive heat dissipation


AISI 316 stainless steel casing for high salinity environments

Light management

Four optics available ensuring maximum design flexibility, protected by 19 mm thick toughened glass




Ghost | Linear profiles | powerLED 6 W 24 V



type		colour			optic	
Steel	CRI 80 88870	3000 K	416 lm	W	20°	20
		4000 K	488 lm	N	50°	50
		5000 K	540 lm	C	Asym.	07
R - G - B - Y on request						

89488	89179	99332	89282	89284	89190
ON/OFF 1 - 2 art.	ON/OFF 1 - 4 art.	1-10V 1 - 25 art.	Outer casing	Outer casing	5 m cable


Ghost | Linear profiles | topLED 12 W 24 V



type		colour			optic	
Steel	CRI 80 88874	3000 K	475 lm	W	Diff.	00
		4000 K	500 lm	N		
		5000 K	525 lm	C		

89179	89488	99332	89282	89284	89190
ON/OFF 1 - 2 art.	ON/OFF 1 art.	1-10V 1 - 12 art.	Outer casing	Outer casing	5 m cable


Ghost | Linear profiles | powerLED 9 W 24 V



type		colour			optic	
Steel	CRI 80 88871	3000 K	624 lm	W	20°	20
		4000 K	732 lm	N	50°	50
		5000 K	810 lm	C	Asym.	07
R - G - B - Y on request						

89488	89179	99332	89283	89285	89190
ON/OFF 1 art.	ON/OFF 1 - 2 art.	1-10V 1 - 16 art.	Outer casing	Outer casing	5 m cable


Ghost | Linear profiles | topLED 18 W 24 V



type		colour			optic	
Steel	CRI 80 88875	3000 K	760 lm	W	Diff.	00
		4000 K	800 lm	N		
		5000 K	840 lm	C		


89179	89359	99332	89283	89285	89190
ON/OFF 1 art.	ON/OFF 1 - 2 art.	1-10V 1 - 8 art.	Outer casing	Outer casing	5 m cable

Ghost | Walk-over outer-casing



type	L. mm	suitable for	
Steel	486	88870 - 88872 - 88874 - 88876	89284
Steel	736	88871 - 88873 - 88875 - 88877	89285

Ghost | Drive-over outer-casing



type	L. mm	suitable for	
Steel	486	88870 - 88872 - 88874 - 88876	89282
Steel	736	88871 - 88873 - 88875 - 88877	89283

Cables | Power 24V DC



connectors	sec. Ø	suitable for	L. m	
F 4 pin M12	4 x 0,5 mm ²	Ghost	1,5	99216
			5	89190

Extension cable | Power 24V DC



connectors	sec. Ø	suitable for	L. m	
M + F 4 pin M12	4 x 0,5 mm ²	Ghost	1	98437
			5	98149
			10	89188

Cables | Power RGB 24V DC



connectors	sec. Ø	suitable for	L. m	
M 5 pin M12	5 x 0,5 mm ²	Ghost RGB	5	89362

Extension cable | Power RGB 24V DC



connectors	sec. Ø	suitable for	L. m	
M + F 5 pin M12	5 x 0,5 mm ²	Ghost RGB	10	89361

