

Ivil



A drive-over uplight **also available in the tilting version**, ideally suited to **illuminate columns and external architectural elements**.

Passive heat dissipation

AISI 316 stainless steel casing for high salinity environments

Light management


Six optics available ensuring maximum design flexibility

Independent power supply

Available in the version with resin-potted driver integrated in the lighting fixture casing



Ivil_R | Drive-over spotlight | 190-250 V | powerLED 2 W 630 mA



type

Grey	CRI 80	97592
Chrome	CRI 80	97591
Steel	CRI 80	97593

colour

3000 K	208 lm	W
4000 K	222 lm	N
5000 K	253 lm	C
R - G - B - Y on request		

optic

15°	15
30°	30
60°	60
120°	12
Diff.	00



84935

Outer casing

Ivil_R | Drive-over spotlight | powerLED 2 W 630 mA



type

Grey	CRI 80	97586
Chrome	CRI 80	97585
Steel	CRI 80	97587

colour

3000 K	208 lm	W
4000 K	222 lm	N
5000 K	253 lm	C
R - G - B - Y on request		

optic

15°	15
30°	30
60°	60
120°	12
Diff.	00



89420

ON/OFF
1 - 2 art.



99179

ON/OFF
3 - 6 art.



99186


ON/OFF
6 - 12 art.



84936

Outer casing

Ivil_R | Drive-over spotlight | powerLED 2 W 630 mA



type

Grey	CRI 80	97084
Chrome	CRI 80	97083
Steel	CRI 80	97085

colour

3000 K	164 lm	W
4000 K	175 lm	N
5000 K	213 lm	C
R - G - B - Y on request		

optic

3°	03
----	-----------



89420

ON/OFF
1 - 2 art.



99179

ON/OFF
3 - 6 art.



99186


ON/OFF
6 - 12 art.



84935

Outer casing

Ivil_R | Drive-over spotlight | 190-250 V | powerLED 2 W 630 mA



type

Grey	CRI 80	97081
Chrome	CRI 80	97080
Steel	CRI 80	97082

colour

3000 K	208 lm	W
4000 K	222 lm	N
5000 K	253 lm	C
R - G - B - Y on request		

optic


Asym.	07
-------	-----------



84935

Outer casing

Ivil_RJ | Drive-over spotlight | 190-250 V | powerLED 2 W 630 mA



type

Grey	CRI 80	97604
Chrome	CRI 80	97603
Steel	CRI 80	97605

colour

3000 K	208 lm	W
4000 K	222 lm	N
5000 K	253 lm	C
R - G - B - Y on request		

optic



15°	15
30°	30
60°	60
120°	12



84935

Outer casing

Ivil_RJ | Drive-over spotlight | powerLED 2 W 630 mA



type

Grey	CRI 80	97598
Chrome	CRI 80	97597
Steel	CRI 80	97599

colour

3000 K	208 lm	W
4000 K	222 lm	N
5000 K	253 lm	C
R - G - B - Y on request		

optic

15°	15
30°	30
60°	60
120°	12



89420

ON/OFF
1 - 2 art.

99179

ON/OFF
3 - 6 art.


99186

ON/OFF
6 - 12 art.

84936

Outer casing

Ivil_RI | Drive-over spotlight | 190-250 V | powerLED 2 W 630 mA



type

Steel	CRI 80	93928
-------	--------	--------------

colour

3000 K	208 lm	W
4000 K	222 lm	N
5000 K	253 lm	C
R - G - B - Y on request		

optic



8°	08
15°	15
30°	30
60°	60



84935

Outer casing

Ivil_RI | Drive-over spotlight | powerLED 2 W 630 mA



type

Steel	CRI 80	93932
-------	--------	--------------

colour

3000 K	208 lm	W
4000 K	222 lm	N
5000 K	253 lm	C
R - G - B - Y on request		

optic

8°	08
15°	15
30°	30
60°	60



89420

ON/OFF
1 - 2 art.

99179

ON/OFF
3 - 6 art.


99186

ON/OFF
6 - 12 art.

84936

Outer casing

Ivil_Q | Drive-over spotlight | 190-250 V | powerLED 2 W 630 mA




type		colour			optic	
Grey	CRI 80 97595	3000 K	208 lm	W	15°	15
Chrome	CRI 80 97594	4000 K	222 lm	N	30°	30
Steel	CRI 80 97596	5000 K	253 lm	C	60°	60
		R - G - B - Y on request			120°	12
					Diff.	00



84935
Outer casing

Ivil_Q | Drive-over spotlight | powerLED 2 W 630 mA



type		colour			optic	
Grey	CRI 80 97589	3000 K	208 lm	W	15°	15
Chrome	CRI 80 97588	4000 K	222 lm	N	30°	30
Steel	CRI 80 97590	5000 K	253 lm	C	60°	60
		R - G - B - Y on request			120°	12
					Diff.	00



89420
ON/OFF
1 - 2 art.



99179
ON/OFF
3 - 6 art.



99186
ON/OFF
6 - 12 art.



84936
Outer casing

Ivil_Q | Drive-over spotlight | powerLED 3 W 350 mA



type		colour			optic	
Grey	86699	RGB		Z	50°	50
Chrome	86698				120°	12
Steel	86700				Diff.	00



99140
N/O & IR



99205
DMX




99201
DMX



84936
Outer casing

Ivil_QJ | Drive-over spotlight | 190-250 V | powerLED 2 W 630 mA





type		colour			optic	
Grey	CRI 80 97607	3000 K	208 lm	W	15°	15
Chrome	CRI 80 97606	4000 K	222 lm	N	30°	30
Steel	CRI 80 97608	5000 K	253 lm	C	60°	60
		R - G - B - Y on request			120°	12



84935
Outer casing

Ivil_QJ | Drive-over spotlight | powerLED 2 W 630 mA



type

type	CRI	code
Grey	80	97601
Chrome	80	97600
Steel	80	97602

colour

colour	temp	lm	code
3000 K	208	lm	W
4000 K	222	lm	N
5000 K	253	lm	C
R - G - B - Y on request			

optic

optic	code
15°	15
30°	30
60°	60
120°	12



89420

ON/OFF
1 - 2 art.

99179

ON/OFF
3 - 6 art.


99186

ON/OFF
6 - 12 art.

84936

Outer casing

Ivil_QI | Drive-over spotlight | 190-250 V | powerLED 2 W 630 mA



type

type	CRI	code
Steel	80	93929

colour

colour	temp	lm	code
3000 K	208	lm	W
4000 K	222	lm	N
5000 K	253	lm	C
R - G - B - Y on request			

optic



optic	code
8°	08
15°	15
30°	30
60°	60



84935

Outer casing

Ivil_QI | Drive-over spotlight | powerLED 2 W 630 mA



type

type	CRI	code
Steel	80	93933

colour

colour	temp	lm	code
3000 K	208	lm	W
4000 K	222	lm	N
5000 K	253	lm	C
R - G - B - Y on request			

optic

optic	code
8°	08
15°	15
30°	30
60°	60



89420

ON/OFF
1 - 2 art.

99179

ON/OFF
3 - 6 art.

99186

ON/OFF
6 - 12 art.

84936

Outer casing

Ivil | Outer-casing



type	Ø mm	h. mm	suitable for	code
PVC	69	92	Ivil (no driver)	84936

Ivil | Outer-casing



type	Ø mm	h. mm	suitable for	code
PVC	69	139	Ivil (driver included)	84935