

## Nero Accent

LED 3000 K

Wall Recessed Luminaire, Floor Recessed Luminaire, Light distribution direct, asymmetric  
Accent Washlights  
Finish in Stainless Steel, Cover clear

Product EL97004-78-W  
Operating Technology 83734  
Note: The components must be ordered separately.

### Light Technique

Colour rendering index CRI > 80  
Colour temperature 3000 K  
50.000 h lifetime (L70)  
Asymmetrical version for step lighting  
LED colour finish optional

### Luminaire housing

Light proof housing made of die cast zinc  
Surface satin stainless steel  
Tempered safety glass, clear  
Protection class IP 67  
Max. load 500 kg

### Operating and assembly technology

LED gear box to be separately  
Round cut-outs also for square luminaires for an easy adjustment  
Identical version for wall and floor luminaires  
Suitable to assemble in raised floor and wall

### Optional equipment

Concrete mounting box 88090R05  
Mounting accessories 88015, 88005R05, 88019

### Light Technique

Lamp Wattage	3 W
Colour Rendering Index	80
Colour Temperature	3000 K
Beam spread angle $\gamma$	asymmetric
Luminaire Luminous Flux	47 Lm
System Efficiency	16 Lm/W
Energy Efficiency Class	A
Number Luminaires LZ	3.60


### Operating technology

Connector	screw connector, 2 x 0.75 mm <sup>2</sup>
Operation Mode	standard, IP67

### Dimensions

Reflector Size	Q05
Length L	78 mm
Width W	78 mm
Cut-out CO	68 mm
Installation Depth RD	45 mm
Total Weight	0.6 kg

The information contained in our datasheets is based on current and relevant information at the time of original issue or publication.  
We constantly strive to improve and upgrade our products from a performance, materials and quality perspective.  
This may result in a difference between actual product performance and that shown on data sheets, warranties are based on actual delivered product performance.



EL97004-78-W

